

TEST REPORT

Job No./Report No: 20-005248

Date: 26/06/2020

SOP305 - Change of appearance after washing (Garments and fabrics)

ID	ID AMSLab	Description	Conclusion
2	S-200603-00013	FABRIC MULTICOLOR (20 WASHING CYCLES AT 60°C)	See Results
ID	ID AMSLab	Description	Conclusion
5	S-200617-00018	FABRIC MULTICOLOR (50 WASHING CYCLES AT 60°C)	See Results
ID	ID AMSLab	Description	Conclusion
8	S-200619-00140	FABRIC MULTICOLOR (25 WASHING CYCLES AT 60°C)	See Results

	CAS	S-200603-00013	S-200617-00018	S-200619-00140
Change of appearance after washing		No change	Slight change	Slight change
Number of cycles		20	50	25
Washing Temperature		60°C	60°C	60°C

Note 1: Washing and drying process applied based on UNE-EN ISO 6330:2012

- Detergent: 20 gr of Commercial detergent / Drying procedure: Air dry without tumble dry.
- n.a.: not applicable
- Requirement: No obvious change/colour/shape/appearance/seams/embroidery/trimmings/applications

Note 3 - Meaning of the grades of change of appearance:

- No change in appearance after washing and drying process
- Slight change in appearance after washing and drying process
- Moderate change in appearance after washing and drying process
- Severe change in appearance after washing and drying process

SOP 342- Bacterial Filtration Efficiency (BFE) - After Washing

ID	ID AMSLab	Description	Conclusio	
3	S-200603-00014	FABRIC MULTICOLOR (AFTER 20 WASHING CYCLES AT 60°C)	See Results	
ID	ID AMSLab	Description	Conclusion	
6	S-200617-00019	FABRIC MULTICOLOR (AFTER 50 WASHING CYCLES AT 60°C)	See Results	
ID	ID AMSLab	Description	Conclusion	
9	S-200619-00141	FABRIC MULTICOLOR (AFTER 25 WASHING CYCLES AT 60°C)	See Results	

- -The laboratory is not responsible for the information received by the client (grey shaded fields)
- -Reported results do not include uncertainties (but are available for the customer).
- -Opinions and interpretations expressed herein are outside the scope of accreditation.
- -Unless otherwise stated the result shown in this test report refer only the sample/s tested and such sample/s are retained for 30 days only.
- -Test reports without AMSLab seal and authorized signatures are invalid.
- -This document can't be reproduced or modified except in full, without prior given approval of the company.
- -Any printed copy of this document is copy from the original digital document.



TEST REPORT

Job No./Report No: 20-005248

26/06/2020 Date:

	CAS	S-200603-00014	S-200617-00019	S-200619-00141
Test 1: Bacterial Filtration Efficiency		84.6	80.6	82.1
Test 1: Number of Bacteria		320	410	380
Test 2: Bacterial Filtration Efficiency		84.6	79.9	82.4
Test 2: Number of Bacteria		326	425	374
Test 3: Bacterial Filtration Efficiency		84.5	79.6	82.7
Test 3: Number of Bacteria		329	435	366
Test 4: Bacterial Filtration Efficiency		84.7	79.8	83.1
Test 4: Number of Bacteria		325	429	358
Test 5: Bacterial Filtration Efficiency		85.0	79.4	83.3
Test 5: Number of Bacteria		318	436	354

Notes:

Test Metod Ref: TS EN 14683:2019 Medical Face Masks, Requirements and Test Methods

Specifications applied:

Spanish specification UNE 0065:2020: ≥ 90%

European specification CWA 17553:2020: Level ≥ 90% and Level ≥ 70%

Report unit Bacterial Filtration Efficiency = % Report unit Number of Bacteria = cfu/mL

A specimen of the mask material is clamped between a impactor and an aerosol chamber. An aerosol of Staphylococcus aureus is introduced into the aerosol chamber and drawn through the mask material and the impactor under vacuum. The bacterial filtration efficiency of the mask is given by the number of colony forming units passing through the medical face mask material expressed as a percentage of the number of colony forming units present in the challenge aerosol.

Test Flow Rate:28,3 L/min Test Flow Time:2 minute Sample Sizes:10x10 cm2

Microorganism:Staphylococcus aureus ATCC 6538 Bacterial concentration (cfu/ml) :5x10E5 cfu/ml Incubation conditions: 24 hour, 35C ± 2C

Positive control sample average of number of Bacteria (C): 2.12x10E3 cfu/ml

(*) Test subcontracted. Results in subcontracted report number: 20018267

SOP106 - Determination of breathability (Differential Pressure) - After Washing

ID ID AMSLab		Description	Conclusion	
1	S-200603-00012	FABRIC MULTICOLOR (AFTER 20 WASHING CYCLES AT 60°C)	See Results Conclusion	
ID	ID AMSLab	Description		
4	S-200617-00017	FABRIC MULTICOLOR (AFTER 50 WASHING CYCLES AT 60°C)	See Results	
ID	ID AMSLab	Description	Conclusion	
7	S-200619-00139	FABRIC MULTICOLOR (AFTER 25 WASHING CYCLES AT 60°C)	See Results	

- -The laboratory is not responsible for the information received by the client (grey shaded fields)
- -Reported results do not include uncertainties (but are available for the customer).
- -Opinions and interpretations expressed herein are outside the scope of accreditation.
 -Unless otherwise stated the result shown in this test report refer only the sample/s tested and such sample/s are retained for 30 days only.
- -Test reports without AMSLab seal and authorized signatures are invalid.
- -This document can't be reproduced or modified except in full, without prior given approval of the company.
- -Any printed copy of this document is copy from the original digital document.



TEST REPORT

·

Job No./Report No: 20-005248

Date: 26/06/2020

1	CAS	S-200603-00012	S-200617-00017	S-200619-00139
Average Differential pressure (Pa/cm2)		16	13	14
Value 1 Differential pressure (Pa/cm2)		16	13	14
Value 2 Differential pressure (Pa/cm2)		16	12	14
Value 3 Differential pressure (Pa/cm2)		17	12	13
Value 4 Differential pressure (Pa/cm2)		16	13	13
Value 5 Differential pressure (Pa/cm2)		17	13	15

Notes:

Note 1: Applied standard UNE-EN 14683:2019 and Specification UNE 0064-1, 0064-2 and 0065

Note 2: Size of test specimen: 4.9 cm2

Note 3: Tested area of the test specimen: 2.5 cm

Note 4: Flow of air: (8 ± 0.2) l/min

Note 5: Velocity of 272 l/m2/s or 272 mm/s

Note 6: Report Unit: Pa and P (Pa/cm2)

Note 7: Number of measurements: 5

Note 8: Conditioned samples: 4 hours at 21 \pm 5 °C and 85 \pm 5 HR

Note 9: n.a. = not applicable

Requirement by standard:

- Non-reusable Hygienic Mask by UNE 0064-1-2: ≤ 60 Pa/cm2

- Reusable Hygienic Mask by UNE 0065: ≤ 60 Pa/cm2

- European specification CWA 17553:2020: ≤ 70 Pa/cm2

Specific Notes:

(**) The result is out of specifications

Issue Date: 26/06/2020

Signed: Manuel Lolo

Signed: Pablo Perez

Signed: Esteban Ramirez

anglab.

General Manager

Chemical Lab Manager

Physical Lab Manager

-Reported results do not include uncertainties (but are available for the customer).

-Opinions and interpretations expressed herein are outside the scope of accreditation.

-Test reports without AMSLab seal and authorized signatures are invalid.

-Any printed copy of this document is copy from the original digital document.

⁻The laboratory is not responsible for the information received by the client (grey shaded fields)

⁻Unless otherwise stated the result shown in this test report refer only the sample/s tested and such sample/s are retained for 30 days only.

⁻This document can't be reproduced or modified except in full, without prior given approval of the company.